

Verde1999

LIVINGSTONE

Livingstone features popular white marbles - from the gentle movement of the Bianco and Gold colors to the stronger veining of the Melange. The antiqued finish gives the appearance of a floor in a historic building that has been aged and worn over time. The technical advantages of an Italian porcelain and the various mosaic options add to the series' allure.



Bianco (VELEBO)



Gold (VELEGD)



Melange (VELEME)



Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout. See reverse side for additional product information.

Product Information

Colors

Bianco (VELEBO)
 Gold (VELEGD)
 Melange (VELEME)

Sizes - Rectified

12 x 24 VELE--/1224

Mosaic


2 x 2 VELE--/22



2 x 2 Mosaic -
 Full Sheet Shown

Basketweave Mosaic - Full sheet shown

VELEB1/BW



Blend 1
 (Bianco/Nero/Nero)

VELEB2/BW



Blend 2
 (Arabescato/Bianco/Grigio)

VELEB4/BW



Blend 4
 (Melange/Gold/Nero)

Trim

Available in all colors. The surface bullnose is made from field tile that is cut, ground and re-glazed.

VELE--/SBN 3 x 24 Surface Bullnose

Usage & Installation Information

Livingstone is suitable for residential to moderate commercial applications.

As with all inkjet products, there are many different graphics that are mixed and packed randomly. It is important to pull from multiple boxes during installation, rotate pieces, and note the placement of the different images to get the proper final blend.

Most Italian manufacturers recommend a maximum offset of 8" (20cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles ANSI A 108.2 Section 4.3.8.

Technical Information

Physical Properties	Norms	Value	Physical Properties	Norms	Value
Deep Abrasion Resistance	10545-6	<175mm ³ Conforms	Dynamic (DCOF) Coefficient of Friction	ANSI A137.1:2012	≥ 0.42 Wet
Water Absorption	10545-3	≤0.5% Conforms	The Dynamic Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs. As noted in the American with Disabilities Act (ADA) the coefficient of friction varies considerably due to facts not under the control of entities such as the manufacturers and distributors. These factors include, but are not limited to, contaminants, slope of terrain, drainage conditions, adjacent surfaces, etc. Suitability for any installation can only be determined by a site examination of all conditions that could affect the slip resistance of the tile being installed. Continual cleaning and maintenance must be performed once the tile has been installed.		
Frost Resistance	10545-12	Resistant			
Slip Resistance	DIN51130R	R10			