

MONOCIBEC

THYMOS

Thymos is inspired by a marble from the Anatolian peninsula that seemingly preserves the breath of the Earth. It is a material of rare beauty that is defined by measured contrasts and an innate refinement. The chromatically uniform background is mottled with delicate nuances, and the foreground has fine and warm veining which runs across the surface in multiple directions. The brushed finish introduces an elegant note of brightness like the soft reflection of filtered light. It recalls the time-worn surfaces and enhances the depth, color tones and graphic details.



This image shows a close up of the brushed, honed finish in bright light.

Colors are intended as a guide only and may vary from actual tile. Sizes listed are nominal. Please check samples before making final selection and to get actual dimensions for layout.

Colors

Product Information



Dorico (MOTSDO)



Tellur (MOTSTR)



Nemes (MOTSNS)

Sizes (Rectified) - Brushed Finish

12 x 24 MOTS--B/1224


24 x 48* MOTS--B/2448

*Due to the special packing required for the large format tiles, orders for the 24x48 size must be for full box quantities only & we are not able to fill orders on the same day as placed.

Mosaic: 3" Hex - Brushed finish, full sheet shown



MOTSDOB/3HX



MOTSNSB/3HX



MOTSTRB/3HX

Trim 3 x 24 Surface Bullnose (Brushed Finish) MOTS--B/SBN

The surface bullnose is made from field tile that is cut, ground and reglazed.

Usage and Installation

Thymos is suitable for both residential and moderate commercial installations that do not require an R rating. To attain the proper mix of graphics and color it is important to pull from multiple boxes during installation, rotate pieces, and note the placement of the different images to get the proper final blend.

Most tile manufacturers recommend a maximum offset of 8" (20 cm) on all large format tiles when setting a running bond. Please refer to ANSI requirements for setting large format tiles, ANSI A 108.2 section 4.3.8. Using a leveling system can improve the installation of this product.

TECHNICAL INFORMATION - BRUSHED FINISH

Physical Properties	Norms	Value	Physical Properties	Norms	Value
Abrasion Resistance	ISO 10545-7	NS: PEI 4 DO/TR: PEI 5	Breaking Strength	10545-4	Conforms
Water Absorption	10545-3	Conforms	Dynamic Coefficient of Friction (DCOF)**	BOT 3000E STANDARD ANSI A326.3	≥ 0.42 Wet
Frost Resistance	10545-12	Resistant			

** These results are for the natural finish and for the normal productions; if there is concern about a particular production, it should be tested. The Dynamic Coefficient of Friction is a general guide only. Testing may vary with different production runs and with different testing labs.